



T20TX-01NKx



T20TX-02NKL



T20TX-03NKx

Transmitter T20TX-0xNKL/NKM:	
Application areas:	Doors, entrances, gates, winches, pumps, lighting, conveyor belts, hydraulics a.o.
Frequency:	NKL transmitter: 433,92 MHz NKM transmitter: 869,85 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Functions:	NKL transmitter: 1, 2 or 3 NKM transmitter: 1 or 3
Output:	Apr. 7 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	exchangeable battery type: CR2032
Power consumption:	Apr. 25 mA
Temperature:	-20° C to +70° C
Weight:	Apr. 50 g incl. battery
Dimensions:	71 x 39 x 13 mm incl. clips
Protection:	IP 65
Recommended receiver:	NKL transmitter: all transmitters system T20 with 433,92 MHz NKM transmitter: all transmitters system T20 with 869,85 MHz

TELE RADIO AB
Sweden, Main office
Tel. +46 (0)31-748 54 60
e-mail: info@tele-radio.com

www.tele-radio.com

TELE RADIO SVERIGE
Sweden
Tel. +46 (0)31-724 98 00
e-mail: sverige@tele-radio.com

TELE RADIO AS
Norway
Tel. +47-6933 4900
e-mail: m.sundt@tele-radio.com

TELE RADIO OÜ
Estonia
Tel. +372 44 511 55
e-mail: m.jyrissoo@tele-radio.com

TELE RADIO BV
Benelux
Tel. +31 -(0)70-419 41 20
e-mail: info@teleradio.nl

TELE RADIO GmbH
Germany
Tel. +49 (0)94 51-944 8 550
e-mail: kontakt@tele-radio.com

TELE RADIO LTD
England
Tel. +44 (0) 1625 509125
e-mail: sales@teleradiouk.com

TELE RADIO LLC
North America & Latin America
Tel. +1 305 459 0763
e-mail: america@tele-radio.com

TELE RADIO ASIA
China
Tel. +86-(0)592-5501697
e-mail: b.sun@tele-radio.cn